

Prestige™

Urban Paver



Classicism and elegance!

The flat, well-defined surfaces of this square paver lend a sophisticated touch to high-traffic locations.

Characteristics

- 2^{3/8} inches (6 cm) thick.
- Available in a Grenart or regular finish.
- Wide selection of bright colors.
- Comes in three sizes, considerably reducing the need for cutting



BOLDUC

Fashioned in line with nature!

TECHNICAL**SPEC SHEET****Leed Certified Pavers**

Leed-certified solar reflectance index
(Granite Gray and Ivory)

Manufactured with 64% recycled materials
(Anthracite and Granite Gray)

COLORS


Anthracite



Salmon



Smoked Gray



Glade Green



Gray



Brown



Granite Gray




Clay Brown



Charcoal



Ivory



Red



Sable Beige



Heritage Pink



Beige Burned



Red and Charcoal



Champlain Beige



Burgundy


NOTE:
We recommend that you use actual samples to
make your final choice.

Prestige™

Urban Paver

NOMINAL DIMENSIONS

HEIGHT X WIDTH X LENGTH		NUMBER OF PIECES	
in.	cm	/ft ²	/m ²
1. 2 ^{3/8} x 3 ^{15/16} x 7 ^{7/8}	6 x 10 x 20	4,6	50
2. 2 ^{3/8} x 7 ^{7/8} x 7 ^{7/8}	6 x 20 x 20	2,3	25
3. 2 ^{3/8} x 11 ^{13/16} x 11 ^{13/16}	6 x 30 x 30	1,0	11,10

**DIMENSIONAL TOLERANCES †**

The permitted dimensional tolerances prescribed by in the CSA A231.2-06 standard are the following:
Length : -1/32 in. to + 5/64 in. (-1 mm to +2 mm)
Width : -1/32 in. to + 5/64 in. (-1 mm to +2 mm)
height : ± 1/8 in. (± 3 mm)

WEIGHT OF PAVERS: 48,1 lb/sq. ft. (235 kg/m²)**PHYSICAL CHARACTERISTICS †**

COMPRESSIVE STRENGTH**	DURABILITY TO FREEZE-THAW CYCLES WITH UTILISATION IN SALINE SOLUTION**	WATER ABSORPTION
7250 Psi (50 Mpa)	Maximum loss of initial weight in saline solution (NaCl 3%): • 0.74oz / pi2 (225 g/m2) after 28 cycles • 1.64oz / pi2 (500 g/m2) after 49 cycles	5% maximum

SPECIFICATION CLAUSE

SPEC. NOTE: Include the following article in part 2- Products of section 02751-Precast Concrete Pavers. It prescribes the choice for BOLDUC Urban Pavers for landscaping purposes. It should describes the geometric and physical characteristics and, also, the type, the dimensions, the color and the

PART 2 - PRODUCTS**2.1 Precast Concrete Urban Pavers**

.1 Precast concrete urban pavers:
to CSA A231.2-06 and the following
prescriptions.

.2 Prestige™ pavers as supplied by BOLDUC.

.1 Thickness: 2^{3/8} in. (6 cm)

.2 Nominal Dimensions: _____

.3 Color: _____

.4 Texture: _____

finish (Grenart or Regular)

INSTALLATION

Refer to the technical service or to Bolduc's website at www.bolduc.ca to obtain the model specification, installation guide or any other technical information.

† Copies of lab tests are available upon request.

** Tests performed as per CSA A231.2-06



BOLDUC
Concrete product manufacturer

1358-2nd Street, Industrial Park, P.O. Box 608,
Sainte-Marie, Beauce, Québec, Canada G6E 3B8

Sainte-Marie: (418) 387-2634
Québec: (418) 692-0855
Toll free Canada: 1-800-463-8966
Toll free USA: 1-800-603-5567
Fax: (418) 387-6438
www.bolduc.us
info@bolduc.us