


Citadin[®] 80 Paver



Simplicity and Refinement

This large-sized paver's straight lines and smooth finish give it a very refined, contemporary touch.

Features

- 3 1/8 inch (8 cm) thick pavers
- Smooth premium  finish
- Choice of 3 colors
- 1 color contributing to LEED program



BOLDUC

Fashioned in line with nature!

TECHNICAL**SPEC SHEET**

Citadin[®] 80 Paver


Pavers contributing to LEED program
 Leed-certified solar reflectance index
 (Granite Gray)

COLORS

Granite Gray



Light Gray



Anthracite

NOTE:

We recommend that you use actual samples to make your final choice.

NOMINAL DIMENSIONS

HEIGHT X WIDTH X LENGTH		NUMBER OF PIECES	
in	cm	/ft ²	/m ²
3 ¹ / ₈ x 15 ³ / ₄ x 23 ⁵ / ₈ in	8 x 40 x 60 cm	0.39	4.17

**DIMENSIONAL TOLERANCES †**

The permitted dimensional tolerances prescribed in the CSA A231.2 standard are the following:
 Length: -1/32 in to 5/64 in (-1 mm to +2 mm)
 Width: -1/16 in to 5/64 in (-1 mm to +2 mm)
 Height: ±1/8 in (±3 mm)

WEIGHT OF PAVERS: 38 lb/sq. ft. (183 kg/m²)

PHYSICAL CHARACTERISTICS † (PAVERS)

COMPRESSIVE STRENGTH**	RESISTANCE TO FREEZE-THAW CYCLES IN A SALINE SOLUTION**	WATER ABSORPTION
7250 Psi (50 Mpa)	Maximum loss of initial weight in saline solution (NaCl 3%): <ul style="list-style-type: none"> • 0.74oz / pi2 (225 g/m2) after 28 cycles • 1.64oz / pi2 (500 g/m2) after 49 cycles 	5% maximum

SPECIFICATION CLAUSE

SPEC. NOTE: Include the following article in Part 2 - Products of section 32 14 13 - Precast Concrete Pavers. It prescribes the choice of BOLDUC pavers for landscaping purposes. It should describe the geometric and physical characteristics and indicate the paver selected, its dimensions, color and finish.

PART 2 - PRODUCTS**2.1 Precast Concrete Pavers**

- .1 Precast concrete pavers complying with CSA A231.2 and the following prescriptions.
- .2 Citadin 80 pavers supplied by BOLDUC.
 - .1 Thickness: 3¹/₈ in. (8 cm)
 - .2 Nominal Dimensions: 3¹/₈ x 15³/₄ x 23⁵/₈ in (8 x 40 x 60 cm)
 - .3 Color: _____
 - .4 Texture: Smooth premium **P** finish

INSTALLATION

Contact the technical service or go to Bolduc's website at www.bolduc.ca to obtain the model specifications, installation guide or any other technical information.

† Copies of lab tests are available upon request.

** Tests performed as per CSA A231.2



BOLDUC
 Concrete product manufacturer

1358-2nd Street, Industrial Park
 Sainte-Marie, Beauce, Québec, Canada G6E 1G8

Sainte-Marie: (418) 387-2634
 Toll free Canada: 1-800-463-8966
 Toll free USA: 1-800-603-5567
 Fax: (418) 387-6438
www.bolduc.ca
www.bolduc.ca
info@bolduc.ca